National
Aerospace
Laboratories

Glass Transition Temperature (Tg) Measurements on Test Laminates Used in HANSA-3 Prototype II Development (Post Curing Effect)

R M V G K RAO, KAVITHA, A VANAJA
F R P Pilot Plant

Project Document RP 9706

DOCUMENTATION SHEET

	NATIONAL AEROSPACE LABORATORIES	Class : Restricted No. of Copies : 10

Title : Glass transition temperature (Tg) measurements on test laminates used in hansa-3 prototype II development (post curing effect)

Author / s : RMVGK Rao, Kavitha, A Vanaja

Division : FRP Pilot Plant	**NAL Project No.** : 1 – 8 – 112 (c)
Document No. : PD RP 9706	**Date of Issue** : December 1997

Contents		Pages	27	Figures	15	Tables	02	Annexures:

External Participation : ----

Sponsor : ----

Approval : Dr. RMVGK Rao
Head, FRP Pilot Plant

Remarks : ----

Keywords: Tg, DSC, Epoxy resin Post cure

Abstract:

For the weight reduction of Hansa-3 prototype I, design consideration were slightly modified to fabricate a new version viz., Hansa-3 prototype II. In connection with this program laminates were fabriacted using LY 5052 system with both carbon tape and glass fabrics for generation of design allowables. They were post cured and tested for mechanical properties as the degree of post cure directly influences the hot wet mechanical properties, the Tg of post cured specimens were monitored for both GFRP and CFRP specimens.